



**LEGEND**

HPG	High pressure gauge
LPG	Low pressure gauge
ATS	Spring type antivibrant mounting ( Opt )
ATV	Rubber type antivibrant mounting ( Opt )

MOD.	EMPTY WEIGHT	OPERATING WEIGHT	HYDRAULIC CONNECTIONS
EEF.400	4900 kg	5080 kg	DN125
EEF.470	5200 kg	5390 kg	DN150

**LIFTING AND CARRIAGE PRECAUTIONS**

- Check the weight on the CE label to select appropriate lift equipment .
- Before lifting the unit make sure that the external panel is firmly fixed in place.
- To use only lifting points provided.
- The chains or slings must be of equal length.
- To use a spread-bar to avoid damage to the unit.
- The movement must be performed with caution and avoid abrupt movements.
- Never move the unit on rollers.
- Never lift the unit using a fork-lift.



X: ELECTRIC FEED HOLE

Scala-Scale	Data-Date	30/03/15	Dis.to-Drawn	B.P.	N°Pezzi
Peso-Weight Kg.	Materiali-Materials				
Denominazione-Denomination					
WATER CHILLERS mod. EEF.400÷470/CS.ST.NT.NP...					
Particolare-Detail					
Overall dimension - Lift Instruction					
FRAME 5000x2210x2450					

<b>HITEMA®</b>	
DIS.-DRAW N.	DIM-EEF-400ST01
Rev.	00
PROGRAM.N.	