



ISV SERIES				
MOD.	LENGTH	EMPTY WEIGHT	OPERATING WEIGHT	HYDRAULIC CONNECTIONS
300	4600 mm	3050 kg	3180 kg	DN125
350	4600 mm	3100 kg	3250 kg	DN125
390	4600 mm	3200 kg	3370 kg	DN150
440	5900 mm	3600 kg	3780 kg	DN150
480	5900 mm	3670 kg	3850 kg	DN150
520	5900 mm	3750 kg	3930 kg	DN150
600	7200 mm	5200 kg	5500 kg	DN200
680	7200 mm	5250 kg	5600 kg	DN200
770	8500 mm	5900 kg	6200 kg	DN200
850	9800 mm	6550 kg	6900 kg	DN200
910	9800 mm	6730 kg	7100 kg	DN200
970	11100 mm	7450 kg	7900 kg	DN200
1030	11100 mm	7700 kg	8200 kg	DN200
1140	12790 mm	9100 kg	9650 kg	DN250

LIFTING AND CARRIAGE PRECAUTIONS

- Check the weight on the CE label to select appropriate lift equipment .
- Before lifting the unit make sure that the external panel is firmly fixed in place.
- To use only lifting points provided.
- The chains or slings must be of equal length.
- To use a spread-bar to avoid damage to the unit.
- The movement must be performed with caution and avoid abrupt movements.
- Never move the unit on rollers.
- Never lift the unit using a fork-lift.

LEGEND

HPG	High pressure gauge (Opt)
LPG	Low pressure gauge (Opt)
ATS	Spring type antivibrant mounting (Opt)
ATV	Rubber type antivibrant mounting (Opt)



Scala-Scale	Data-Date	Dis.to-Drawn	N°Pezzi	HITEMA [®]
	09/10/18	B.P.		
Peso-Weight Kg.	Materiali-Materials			DIS.-DRAW N.
Denominazione-Denomination				DIM-ISV-001ST01
WATER CHILLERS ISV SERIES				Rev.
Particolare-Detail				00
Overall dimension - Lift Instruction				PROGRAM.N.
FRAME 4600÷12790x2210x2500				