



LEGEND

HPG	High pressure gauge (Opt)
LPG	Low pressure gauge (Opt)
ATS	Spring type antivibrant mounting (Opt)
ATV	Rubber type antivibrant mounting (Opt)

LIFTING AND CARRIAGE PRECAUTIONS

- Check the weight on the CE label to select appropriate lift equipment .
- Before lifting the unit make sure that the external panel is firmly fixed in place.
- To use only lifting points provided.
- The chains or slings must be of equal length.
- To use a spread-bar to avoid damage to the unit.
- The movement must be performed with caution and avoid abrupt movements.
- Never move the unit on rollers.
- Never lift the unit using a fork-lift.



X: ELECTRIC FEED HOLE

NOVAF SERIES				
MOD.	LENGTH	EMPTY WEIGHT	OPERATING WEIGHT	HYDRAULIC CONNECTIONS
663/F4	3100 mm	2900 kg	3100 kg	DN125
683/F6	4050 mm	3800 kg	4050 kg	DN125
693/F6	4050 mm	3900 kg	4150 kg	DN125
773/F6	4050 mm	4050 kg	4300 kg	DN125
783/F8	5000 mm	4650 kg	5050 kg	DN150
793/F8	5000 mm	4800 kg	5200 kg	DN150
863/F8	5000 mm	4950 kg	5400 kg	DN150
873/F10	5950 mm	5500 kg	6100 kg	DN150
883/F12	6900 mm	6300 kg	6900 kg	DN150
893/F14	7850 mm	7400 kg	8050 kg	DN200
963/F16	8800 mm	8500 kg	9200 kg	DN200
973/F18	9750 mm	9500 kg	10200 kg	DN200
983/F20	10700 mm	10400 kg	11100 kg	DN200
993/F22	11650 mm	11400 kg	12150 kg	DN200
9103/F22	11650 mm	11700 kg	12450 kg	DN200

Scala-Scale	Data-Date	Dis.to-Drawn	N°Pezzi	HITEMA [®]
	08/10/18	B.P.		
Peso-Weight Kg.	Materiali-Materials			DIS.-DRAW N.
Denominazione-Denomination				DIM-NOVAF-001ST01
WATER CHILLERS NOVAF Series				Rev.
Particolare-Detail				00
Overall dimension - Lift Instruction				PROGRAM.N.
FRAME 3100÷11650x2210x2500				